


G5.SRC.18.500.108

Programmable DC Power Supply



Key Values

Power		18 kW
Voltage DC	limited by P_{max}	500 V
Current	limited by P_{max}	0...108 A
Autoranging factor	$U_{max} \times I_{max} / P_{max}$	3
<i>Figure 1</i>		
Master-slave / multi-device configuration		series, parallel, mixed
Max. number of devices in system		44
Max. number in parallel		44
Max. number in series	with midpoint earthing limited by output isolation to PE	6
Case		19" / 4U

AC Lineside Rating

Mains connection type	delta	3L + PE (no neutral necessary)
Rated voltage		3 × 380...480 VAC ±10%
Rated current	@nominal 3 × 380 VAC	29 A _{rms}
	@nominal 3 × 400 VAC	28 A _{rms}
	@nominal 3 × 415 VAC	27 A _{rms}
	@nominal 3 × 440 VAC	25 A _{rms}
	@nominal 3 × 460 VAC	24 A _{rms}
	@nominal 3 × 480 VAC	23 A _{rms}
Rated frequency		50/60 Hz
Power factor	@ P_{max}	0.99
THDi	@90% P_{max}	≤3%
Inrush current		33 A _{max rms}
Efficiency	P_{max} @ U_{max}	96%
	P_{max} @ I_{max}	95%
Standby power		31 W
Isolation	AC terminals to PE	900 VDC
	AC to DC terminals	1500 VDC
Input insulation test voltage	line to case/logic	3100 VDC (2s)
Protective earth conductor current	According to IEC 60990	<7 mA @50 Hz
Touch current unweighted	output ON/OFF	≤1.8 mA / 3.4 mA
Touch current weighted	output ON/OFF	≤0.8 mA / 3.2 mA
Input filter discharge	L-PE / L-L	<20 s
<i>to <60 V</i>	with option XCD	<1 s

DC Operation

Operation modes		source
Voltage regulation	CV	0...100% U_{max}
Current regulation	CC	0...100% I_{max}
Power regulation	CP	5...100% P_{max}
Internal resistance simulation	programmable	0...9259 mΩ
Static accuracy		
<i>At 25° ambient temperature, constant line / load conditions, after 1h warm up time in voltage on state, normal distribution (k=2)</i>		
	power @ I_{max} 1 kHz Filter	0.03% FS
	voltage	0.01% FS
	voltage sense	0.01% FS
	current full range 1 kHz Filter	0.025% FS

DC Operation (continued)

Static accuracy <i>At 25° ambient temperature, constant line / load conditions, after 1h warm up time in voltage on state, normal distribution (k=2)</i>	current low range (-10%...10% FS) 1 kHz Filter	0.003% FS
	resistance @ I _{max} 1 kHz Filter	0.03% FS
HMI touchpanel meter resolution	programming/reading	0.01 V 0.01 A
	X-capacitor LowCap	24 µF
Output capacitance	X-capacitor HighCap	444 µF
	Y-capacitor @DC	144 nF
Ripple, voltage	output voltage ripple (<1 MHz): V _{rms} LowCap, ohmic load 90% P _{max} , 90% U _{max} CV mode	≤0.03% FS
	output voltage ripple (<1 MHz): V _{rms} HighCap, ohmic load 90% P _{max} , 90% U _{max} CV mode	≤0.01% FS
	output Current ripple (<1 MHz): A _{rms} LowCap, ohmic load 90% P _{max} , 90% I _{max} CC mode	≤0.05% FS
	noise (20 kHz...20 MHz): V _{pp} LowCap, ohmic load 90% P _{max} , 90% U _{max} CV mode	≤0.2% FS
Noise	noise (20 kHz...20 MHz): V _{pp} HighCap, ohmic load 90% P _{max} , 90% U _{max} CV mode	≤0.1% FS
Stability/drift <i>8h, after 1h warm up time in voltage on state, at constant line input, load and temp. conditions</i>	voltage	≤0.01% FS
	voltage sense	≤0.01% FS
	current	≤0.01% FS
Temperature coefficient <i>At constant line and load conditions</i>	voltage	≤0.005% FS/°C
	voltage sense	≤0.007% FS/°C
	current	≤0.005% FS/°C
Rise/fall time (10...90% of step) <i>Voltage set-value step, const. R load, LowCap</i>	voltage step (0...90% U _{max} / 90% P _{max})	≤170 µs
	current step (10...90% I _{max} , @33% U _{max}) 10...90% of step / settling time	20 µs / 70 µs
Transient response time <i>Load step, ohmic load, HighCap</i>	CV, recovery within 0.5% set voltage 0...90% P _{max} @90% U _{max}	≤200 µs
	CC, recovery within 2% of set current 45...90% P _{max} @90% I _{max}	≤250 µs
Transient response time <i>Load step, ohmic load, LowCap</i>		
	45...90% P _{max} @90% U _{max}	≤0.6% FS
Voltage drop <i>while load switching on HighCap mode</i>		
Voltage overshoot <i>while load switching off HighCap mode</i>	90...45% P _{max} @90% U _{max}	≤0.7% FS
Pulsating load <i>max. load ripple current sine max. amplitude</i>	HighCap	30% I _{max} @3 kHz 26% I _{max} @≥5 kHz
	LowCap	46% I _{max} @3 kHz 17% I _{max} @≥5 kHz

DC Operation (continued)

Max. ripple <i>DC+ to PE / DC- to PE</i>	max. allowed ripple V_{rms} ≤ 1 kHz: $1050 V_{rms}$ >1 kHz: $((1.26 \times 10^6)/f+5) V_{rms}$	≤ 1 kHz: $1050 V_{rms}$ 2 kHz: $630 V_{rms}$ 5 kHz: $250 V_{rms}$ 10 kHz: $130 V_{rms}$ 20 kHz: $65 V_{rms}$ 50 kHz: $30 V_{rms}$ 80 kHz: $20 V_{rms}$
Protection	OVP (over voltage protection) OCP (over current protection) OPP (over power protection) OTP (over temperature protection)	programmable programmable programmable ✓
Output discharge <i>to <60V</i>	active discharge enabled active discharge disabled	<1 s <60 s
Small signal modulation <i>Voltage Controller LowCap mode</i>	frequency CV, CC max. output voltage rms sine @10 kHz attenuation @5 kHz / 10 kHz op. point: 90% U_{nom} + 5% U_{nom} ampl. phase lag analog input to voltage out	0...10 kHz 0...5% FS -0.4 dB / -6 dB 130 μ s
Small signal modulation <i>Current controller LowCap mode</i>	max. output amplitude current @10 kHz attenuation @5 kHz / 10 kHz op. point: 90% I_{nom} + 5% I_{nom} ampl. phase lag analog input to current out	0...5% FS -1.8 dB / -3.8 dB 110 μ s
Sense voltage compensation		Programmable Uout + Udrop limited by $U_{out,max}$
Sense input impedance	@operation @output off no RPP or RPP closed @output off and activated "disconnect output measurement at voltage-off" feature	632 k Ω 632 k Ω >10 M Ω
Ballast resistor DC power port	@output off no RPP or RPP closed @output off RPP, disconnect output measurement at voltage-off deactivated @output off RPP, disconnect output measurement at voltage-off activated	37 k Ω 632 k Ω >10 M Ω
Resistance	DC+/DC- output to PE X713 jumper inserted DC+/DC- output to PE X713 jumper removed	22 M Ω open
Output isolation	DC+/DC- output to PE	1500 VDC
Output insulation test voltage	output to case/logic	3400 VDC (2s)

Various

Case dimensions <i>Figure 3</i>	H x W x D without terminals	178 x 483 x 672 [mm] 7" x 19" x 26 1/2"
Weight		50 kg
AC terminals		screw terminals for 6...25 mm ² wires
DC terminals		output bars for M8 bolts
Communication interface	speed depending on bus load	Ethernet (max. 800 x 16 bit/s), USB (max. 450 x 16 bit/s)
Enclosure	rating	IP20
Option cards	# of free slots	2

Analog Inputs

Number of inputs		4
Resolution		16 Bit
Sampling rate		48 kS/s
Input voltage range	selectable	-10...10 V; -5...5 V; 0...5 V; 0...10 V
Accuracy		bipolar range: ±0.1%, unipolar range: ±0.2%
Input impedance		1 MΩ
Absolut max. input voltage		±30 VDC
Input filter		2nd order low pass filter, cutoff frequency: 15 kHz
Delay analog in to power out		89 μs
Temperature coefficient		0.02% FS/°C

Analog Outputs

Number of outputs		4
Resolution		16 Bit
Update rate		48 kS/s
Settling time		10 μs
Output voltage range	selectable	-10...10 V; -5...5 V; 0...5 V; 0...10 V
Accuracy		±0.2%
Output impedance		0.5 Ω
Max. output current	short-circuit proof	20 mA
Delay power out to analog out		42 μs
Temperature coefficient		0.02% FS/°C

Digital I/O

Number of digital inputs/outputs	programmable (each can be used as input or output)	6
Output voltage supplied for digital I/O		24 VDC (-15%/+20%)
Digital input characteristic		IEC 61131-2 Type 1
Digital input filter		3.2 ms (10 μs, 1 ms, and 10 ms factory configurable)
Max. voltage digital inputs		30 VDC
Sampling rate digital inputs		1 kS/s
Digital output type		high-side switch
Load type		ohmic, inductive, lamp load
Max. total output current (all channels)		0.65 A
Max output current per channel	short-circuit proof	0.625 A
Digital output switching time		T _{ON} : 64...120 μs, T _{OFF} : 90...170 μs
Update rate digital outputs		1 kS/s

Relay Outputs

Number of relay outputs		2 x SPST (NO), 1 x SPDT
Load type		ohmic, inductive, lamp load
Max. switching voltage		30 VDC
Max. switching current		SPST: 3 A, SPDT: 1 A
Switching time		typ. 20 ms

Ambient

Operating altitude	above sea level above 1000 m, slight temp. derating possible	≤2000 m
Operating temperature		-5...50 °C
	with airfilter	-5...40 °C
Storage temperature		-25...70 °C
Installation	IEC 60721-3-3	indoor, air-conditioned in 19" switch cabinet
Orientation	storage, installation, operation	upright
Relative humidity	non-condensing	0...95%
Vibration	IEC 60068-2-6	Test Fc
Cooling		direct forced air, front to back
Acoustic noise level	90% P _{max} , 90% I _{max} 1 m dist. front (typ.)	@25 °C ambient ≤54 dB

Ambient (continued)

Acoustic noise level <i>1 m dist. front (typ.)</i>	90% P _{max} , 90% I _{max} @40 °C ambient	≤71 dB
--	---	--------

Standards

Protection Class	EN 62477-1	1
Degree of pollution	EN 60664-1	2
Overvoltage category	mains input, EN 60664-1 other interfaces	3 2
Area of application		industrial
Approval		CE Marking
EN 62477-1:2012	Low Voltage Directive 2014/35/EU	✓
EN 61010-1:2010	Low Voltage Directive 2014/35/EU	✓
EN ISO 13849-1:2015	w/o ISR with ISR 2-channel with ISR 2-channel and external safety relay	- PL c PL e
EN 61000-6-4:2007 A1:2011	Directive 2014/30/EU EMC emission (industrial)	✓
EN 61000-6-2:2005	Directive 2014/30/EU EMC immunity (industrial)	✓
EN 61326-1:2013	Directive 2014/30/EU EMC industrial level A	✓
EN IEC 63000:2018	RoHS Directive	✓

Operating area




Figure 1: G5.SRC.18.500.108, voltage/current operating area.

Dimensions




Figure 3: Front, right hand side and rear view. 19-inch module with 4 units in height.

For further information to included features see related product description <PD_G5.SRC....> on www.regatron.com
This product is developed, produced and tested according to ISO 9001 by REGATRON.

For detailed technical information, contact REGATRON or your local sales partner.

Regatron AG Feldmuehlestrasse 50 9400 Rorschach SWITZERLAND	Regatron Inc. 100 Overlook Center, 2 nd Floor Princeton, NJ 08540 USA
sales@regatron.com www.regatron.com	inquiries@us.regatron.com www.us.regatron.com

All product specifications and information contained herein are subject to change without notice.

Filename: DS_G5.SRC.18.500.108_EN_220519.pdf

Class: Project specific use only

T012